

IP44 PORCH LANTERNS

- Attractive traditional design
- Manual override on PIR versions



PL6PIRW



PL6PIRB



PL6W



PL6B

	PL6PIRB	PL6PIRW	PL6B	PL6W
Product Finish	Black	White	Black	White
Product Dimensions	367mm Height x 177mm width x 207mm Depth			
Product weight	604g	604g	560g	560g
Barcode	5012739637476	5012739637469	5012739637452	5012739637445
IP Rating	IP44	IP44	IP44	IP44
Lamp Type	42W Halogen or 14W CFL	42W Halogen or 14W CFL	42W Halogen or 14W CFL	42W Halogen or 14W CFL
Beam Angle	360°			
Time Delay	5 secs to 6 min (+/- 2 min)	5 secs to 6 min (+/- 2 min)	-	-
Ambient Light	<10 Lux ~ 2000 Lux	<10 Lux ~ 2000 Lux	-	-
Detection Dist	Max. 8+/-2m	Max. 8+/-2m	-	-
Detection Range	140°	140°	-	-
Installation height	0.5 - 3.5M	0.5 - 3.5M	-	-
Power Consumption	0.45W (Static 0.1W)	0.45W (Static 0.1W)	-	-
Detection Motion Speed	0.6 - 1.5m/s	0.6 - 1.5m/s	-	-
Voltage	230V AC - 50Hz	230V AC - 50Hz	230V AC - 50Hz	230V AC - 50Hz
Main housing material	Rust proof rugged polycarbonate	Rust proof rugged polycarbonate	Rust proof rugged polycarbonate	Rust proof rugged polycarbonate
Fixings	2 x 30mm			
Guarantee	1 Year	1 Year	1 Year	1 Year
Certification & Conformity	BS EN 60598-2-1	BS EN 60598-2-1	BS EN 60598-2-1	BS EN 60598-2-1

