

MECHANICAL THERMOSTATS



GreenBrook are pleased to introduce the 'KingShield' range of thermostats. In addition to the room thermostats, the range includes two froststats and a cyclinder/pipe stat.

- 3 wire operation



TH90-C



TH90C-C



TH90T-C



TH90F-C



TH90FT-C



TH90CS-C

	TH90-C	TH90C-C	TH90T-C	TH90F-C	TH90FT-C	TH90CS-C
Product Finish	White	White	White	White	White	White
Description	Break on rise	Changeover contact	Tamperproof Break on rise	Froststat - For frost protection of building fabric, contents and exposed pipework	Froststat Tamperproof - For frost protection of building fabric, contents and exposed pipework	Cylinder/Pipe Stat - Control for boilers and central heating
Product Dimensions	H83 x W83 x D34mm	H83 x W83 x D34mm	H83 x W83 x D34mm	H83 x W83 x D34mm	H83 x W83 x D34mm	H120 x W40 x D40mm
Product weight	90 gms	90 gms	81 gms	90 gms	81 gms	220 gms
Barcode	5012739640407	5012739640414	5012739640452	5012739640438	5012739640445	5012739640421
IP Rating	IP20	IP20	IP20	IP20	IP20	IP20
Class	II	II	II	II	II	II
Operating Temperature	+5°C to +35°C	+5°C to +35°C	+5°C to +35°C	-5°C to +15°C	-5°C to +15°C	+20°C to +90°C
Voltage	230V AC	230V AC	230V AC	230V AC	230V AC	230V AC
Max Load	Resistive 10A opening	Resistive 10A opening, 3A closing	Resistive 10A opening,	Resistive 10A opening	Resistive 10A opening,	Resistive 15A opening, 15A closing
Guarantee	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year
Certification & Conformity	EN 60730-1/ EN 60730-2-7	EN 60730-1/ EN 60730-2-7	EN 60730-1/ EN 60730-2-7	EN 60730-1/ EN 60730-2-7	EN 60730-1/ EN 60730-2-7	EN 60730-1/ EN 60730-2-7

