



Kingshield

SAFETY AND INSTALLATION INSTRUCTIONS FOR BATHROOM SINGLE & DUAL VOLTAGE SHAVER LIGHT - Model No. STA4

SAFETY INSTRUCTIONS

IMPORTANT

This unit should be installed to current IET wiring regulations, if in doubt consult a qualified electrician.

1. Disconnect from the mains supply before proceeding with the installation.
2. These products should be connected to a lighting circuit or fused at a maximum of 5A.
3. The transformer incorporated in these products has an isolating 20VA loading and an output of 230V and 115V on the dual voltage version and 230V on the single.
4. Please check with the manufacturers instructions for suitability with rechargeable shavers.

INSTALLATION INSTRUCTIONS

These units must be mounted horizontally on a vertical surface. Please read the instructions fully before attempting installation and retain for future reference.

1. Remove the diffuser by gently pressing the sides at the point indicated, in Fig.1, and lift out.
2. Remove the 60 watt 284mm tube by gently pushing



Fig.1

it sideways into the right hand or left hand socket and removing it from the sockets See Fig. 2




Fig. 2

3. Remove the back plate of the shaver light and using a template mark fixings in the required position on the wall, and drill fixing holes accordingly.
4. Connect the cable by passing through the hole in the back plate and follow the codes as listed:
Live (L) = Brown or Red, Neutral (N) = Blue or Black, conductor size 0.5mm to 1.5mm solid or stranded, ensure that no strands of cable are visible outside the connector.
5. Place shaver light into position with black plate secured and screw into wall with appropriate screws through the holes in the base of the unit.
6. Replace the lamp and diffuser.
7. Switch back on the mains supply and shaver light is now ready for use.

Before plugging in the shaver, select the correct output voltage (230 or 115) with the switch provided (dual voltage version only).

TECHNICAL DATA

Power Rating:	230V 50Hz supply 115/230V output
IP Rating:	IP20
F Marked:	Can be mounted on flammable surfaces
Transformer:	20VA overload protected
Insulation:	Double insulated class II transformer
Diffuser:	Safety interlocked
Lamp Type:	60W 284mm double cap striplight
Lamp Output.	
Average Life:	1000 hours
Lampholder:	S15
Lumen output:	500
Colour Temp:	2500 - 3000K
Lamp Size:	284 length \pm 1mm 26 Dia \pm 1mm
Dimmable:	Yes
Energy Consumption:	60 KWH/1000 hours
Energy rating:	E
CRI:	>80

GUARANTEE

Your KingShield Bathroom Shaver Light is guaranteed for 12 months from the date of purchase.

This is in addition to your statutory rights.

PLEASE KEEP THESE INSTRUCTIONS SAFE FOR FUTURE REFERENCE



EMC  **CE**

**GREEN
BROOK**
ELECTRICAL PLC
WEST ROAD . HARLOW
ESSEX . CM20 2BG . UK
sales@greenbrook.co.uk
www.greenbrook.co.uk

Issue No: 703967